



10793 State Route 37 W
 Sunbury, OH 43074
 www.bry-air.com

Toll-Free: (877) 427-9247
 Phone: (740) 965-2974
 Fax: (740) 965-5470

Technical Resource Center

Temperature Conversion Table								
TO	TO	TO	TO	TO	TO	TO	TO	TO
°C	CONVERT ° F or ° C	° F	°C	CONVERT ° F or ° C	° F	°C	CONVERT ° F or ° C	° F
- 45.66	- 50	- 58.0	- 6.11	21	69.8	22.22	72	161.6
- 42.77	- 45	- 49.0	- 5.56	22	71.6	22.78	73	163.4
- 40.00	- 40	- 40.0	- 5.00	23	73.4	23.33	74	165.2
- 37.23	- 35	- 31.0	- 4.44	24	75.2	23.89	75	167.0
-34.44	- 30	- 22.0	- 3.89	25	77.0	24.44	76	168.8
- 31.66	- 25	- 13.0	- 3.33	26	78.8	25.00	77	170.6
- 31.11	- 24	- 11.2	- 2.78	27	80.6	25.56	78	172.4
- 30.55	- 23	- 9.4	- 2.22	28	82.4	26.11	79	174.2
- 30.00	- 22	- 7.6	- 1.67	29	84.2	26.67	80	176.0
- 29.45	- 21	- 5.8	- 1.11	30	86.0	27.22	81	177.8
- 28.89	- 20	- 4.0	- 0.56	31	87.8	27.78	82	179.6
- 28.34	- 19	- 2.2	0	32	89.6	28.33	83	181.4
- 27.78	- 18	- 0.4	0.56	33	91.4	28.89	84	183.2
- 27.23	- 17	1.4	1.11	34	93.2	29.44	85	185.0
- 26.67	- 16	3.2	1.67	35	95.0	30.00	86	186.8
- 26.12	- 15	5.0	2.22	36	96.8	30.56	87	188.6
- 25.56	- 14	6.8	2.78	37	98.6	31.11	88	190.4
- 25.00	- 13	8.6	3.33	38	100.4	31.67	89	192.2
-24.44	- 12	10.4	3.89	39	102.2	32.22	90	194.0
- 23.88	- 11	12.2	4.44	40	104.0	32.78	91	195.8
- 23.33	- 10	14.0	5.00	41	105.8	33.33	92	197.6
- 22.77	- 9	15.8	5.56	42	107.6	33.89	93	199.4
- 22.22	- 8	17.6	6.11	43	109.4	34.44	94	201.2
- 21.67	- 7	19.4	6.67	44	111.2	35.00	95	203.0
- 21.11	- 6	21.2	7.22	45	113.0	35.56	96	204.8
- 20.56	- 5	23.0	7.78	46	114.8	36.11	97	206.6
- 20.00	- 4	24.8	8.33	47	116.6	36.67	98	208.4
- 19.44	- 3	26.6	8.89	48	118.4	37.22	99	210.2
- 18.89	- 2	28.4	9.44	49	120.2	37.78	100	212.0
- 18.33	- 1	30.2	10.00	50	122.0	43.33	110	230.0
- 17.78	0	32.0	10.56	51	123.8	48.89	120	248.0
- 17.22	1	33.8	11.11	52	125.6	54.44	130	266.0
- 16.67	2	35.6	11.67	53	127.4	60.00	140	284.0
- 16.11	3	37.4	12.22	54	129.2	65.56	150	302.0
- 15.56	4	39.2	12.78	55	131.0	71.11	160	320.0
- 15.00	5	41.0	13.33	56	132.8	76.67	170	338.0
- 14.44	6	42.8	13.89	57	134.6	82.22	180	356.0
- 13.89	7	44.6	14.44	58	136.4	87.78	190	374.0
- 13.33	8	46.4	15.00	59	138.2	93.33	200	392.0
- 12.78	9	48.2	15.56	60	140.0	98.89	210	410.0
- 12.22	10	50.0	16.11	61	141.8	104.44	220	428.0
- 11.67	11	51.8	16.67	62	143.6	110.00	230	446.0
-11.11	12	53.6	17.22	63	145.4	115.56	240	446.0
- 10.56	13	55.4	17.78	64	147.2	121.11	250	482.0
- 10.00	14	57.2	18.33	65	149.0	126.67	260	500.0
- 9.44	15	59.0	18.89	66	150.8	132.22	270	518.0
- 8.89	16	60.8	19.44	67	152.6	137.78	280	536.0
- 8.33	17	62.6	20.00	68	154.4	143.33	290	554.0
- 7.78	18	64.4	20.56	69	156.2	148.89	300	572.0
- 7.22	19	66.2	20.11	70	158.0			
- 6.67	20	68.0	21.67	71	159.8			